1	HOUSE BILL NO. 586
2	INTRODUCED BY M. LEE, J. REAVIS, B. EDWARDS, J. ISALY, P. STRAND, T. CROWE, J. SECKINGER, B.
3	CLOSE, P. ELVERUM, S. FYANT, J. WEBER, J. SOOKTIS, A. GRIFFITH, M. CUNNINGHAM, E. TILLEMAN,
4	E. MATTHEWS, T. RUNNING WOLF, F. SMITH, M. FOX, K. ZOLNIKOV, D. BAUM, M. CAFERRO, B.
5	CARTER, J. COHENOUR, N. DURAM, D. HAWK, S. HOWELL, J. KARLEN, C. KEOGH, M. ROMANO, E.
6	STAFMAN, K. SULLIVAN, Z. ZEPHYR, M. MARLER, S. DEMAROIS, D. JOY, C. FITZPATRICK
7	
8	A BILL FOR AN ACT ENTITLED: "AN ACT REVISING CHILD SAFETY RESTRAINT SYSTEM LAWS;
9	REQUIRING THE USE OF A CHILD SAFETY RESTRAINT SYSTEM FOR CHILDREN UNDER CERTAIN AGE
10	THRESHOLDS 6 YEARS OF AGE; PROVIDING EXEMPTIONS FOR CERTAIN VEHICLES AND
11	CIRCUMSTANCES FROM CHILD SAFETY RESTRAINT SYSTEM LAWS; PROVIDING DEFINITIONS; AND
12	AMENDING SECTIONS 61-9-419, 61-9-420, AND 61-9-421, MCA."
13	
14	BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF MONTANA:
15	
16	Section 1. Section 61-9-419, MCA, is amended to read:
17	"61-9-419. "Properly restrained" defined <u>Definitions</u> . (1) As used in 61-9-420 through 61-9-423
18	and this section, unless the context requires otherwise, the following definitions apply:
19	(a) "Booster seat" means a child safety restraint system that meets applicable federal motor
20	vehicle safety standards and is designed to provide belt-positioning that elevates a child to be properly seated
21	with a safety belt.
22	(b) "Child safety restraint system" means a device that:
23	(i) meets applicable federal motor vehicle safety standards; and
24	(ii) is appropriate to the age of the child being restrained, as provided in 61-9-420.
25	(c) (i) "properly restrained" "Properly restrained" means fastened in a manner prescribed by the
26	manufacturer of the child safety restraint system that permits the child safety restraint system to act as a body
27	restraint <del>, but.</del>
28	(ii) The term does not mean a system in which the only body restraint is a safety belt of the type



1	required by 61-9-409.
2	(d) "Secured with a safety belt" means restrained or secured by a seat belt that:
3	(i) meets applicable federal motor vehicle safety standards; and
4	(ii) is properly adjusted and fastened WITH THE LAP STRAP ACROSS THE HIPS AND THE SHOULDER
5	STRAP ACROSS THE CHEST, including both the shoulder and lap straps, when equipped in the vehicle."
6	
7	Section 2. Section 61-9-420, MCA, is amended to read:
8	"61-9-420. Child safety restraint systems standards exemptions. (1) EACH MOTOR VEHICLE
9	PASSENGER WHO IS UNDER 6 YEARS OF AGE AND WEIGHS LESS THAN 60 POUNDS MUST BE TRANSPORTED AND
10	PROPERLY RESTRAINED IN A CHILD SAFETY RESTRAINT SYSTEM. THE CHILD SAFETY RESTRAINT SYSTEM MUST BE
11	APPROPRIATE FOR THE HEIGHT AND WEIGHT OF THE CHILD, AS INDICATED BY MANUFACTURER STANDARDS, AND COMPLY
12	WITH FEDERAL MOTOR VEHICLE SAFETY STANDARDS. Each motor vehicle passenger who is under 6 years of age
13	and weighs less than 60 pounds must be transported and properly restrained in a child safety restraint. The
14	child safety restraint must be appropriate for the height and weight of the child as indicated by manufacturer
15	standards. A motor vehicle passenger who is under 2 years of age must be properly restrained in a rear-facing
16	child safety restraint system that complies with federal motor vehicle safety standards.
17	(2) A motor vehicle passenger who is between 2 years of age and up to 4 years of age must be
18	properly restrained in a rear-facing or forward-facing child safety restraint system with an internal harness that
19	complies with federal motor vehicle safety standards.
20	(3) A motor vehicle passenger who is between 4 years of age and up to 8 years of age must be
21	properly restrained in a forward-facing child safety restraint system with an internal harness or a child booster
22	seat that is secured with a vehicle lap-shoulder seat belt, whichever is applicable, that complies with federal
23	motor vehicle safety standards.
24	(4) A motor vehicle passenger who is at least 9 years of age or has outgrown the height or weight
25	limits of a child booster seat as set by the manufacturer, whichever comes first, must be secured with a motor
26	vehicle adult safety belt.
27	(5)(2) A child safety restraint system pursuant to 61-9-419 through 61-9-423 must be installed,
28	adjusted, and used according to the manufacturer instructions.



1	(2) The department shall by rule establish standards in compliance with 61-9-419 through 61-9-
2	423 and applicable federal standards for approved types of child safety restraint systems.
3	(3)(6)(3) The department may by rule exempt from the requirements of subsection (1) this
4	section a child who because of a physical or medical condition or body size cannot be placed in a child safety
5	restraint_system."
6	
7	Section 3. Section 61-9-421, MCA, is amended to read:
8	"61-9-421. Certain vehicles exempt. Section 61-9-420 is not applicable to a vehicle that as follows
9	(1) <u>if a vehicle</u> is a motorbus MOTOR HOME, schoolbus SCHOOL BUS, taxicab, <u>farm tractor</u> , bicycle,
10	moped, quadricycle, or motorcycle, or motor-driven cycle or is not required to be equipped with safety belts
11	under 49 CFR 571 as it reads on January 1, 1984 January 3, 2025;
12	(2) if a vehicle is an ambulance or other emergency vehicle designated or authorized by the
13	department; or
14	(2) has a seating capacity as designated by the manufacturer of two persons and there are two
15	persons 4 years of age or older in the vehicle.
16	(3) if an emergency exists that threatens the life of a person operating a motor vehicle to whom
17	this section would otherwise apply or the life of a child who would otherwise be required to be properly
18	restrained as provided in 61-9-420."
19	- END -

